

# S6-GR1P(2.5-6)K

Solis Single Phase Inverters



360 degree

## Features:

- ▶ Max. efficiency 97.7%
- ▶ String current up to **14A**
- ▶ Super high frequency switching technology
- ▶ Wide voltage range and low startup voltage
- ▶ 2 MPPT design with precise MPPT algorithm
- ▶ Intergrated Export Power Manager (EPM)
- ▶ Integrated AFCI (DC arc-fault circuit protection)
- ▶ Compact and lightweight
- ▶ Friendly and adaptable connection to the grid



## Model:

S6-GR1P2.5K S6-GR1P3K S6-GR1P3.6K  
S6-GR1P4K S6-GR1P4.6K S6-GR1P5K  
S6-GR1P6K

## Datasheet

Model Name	S6-GR1P2.5K	S6-GR1P3K	S6-GR1P3.6K	S6-GR1P4K	S6-GR1P4.6K	S6-GR1P5K	S6-GR1P6K
------------	-------------	-----------	-------------	-----------	-------------	-----------	-----------

### Input DC

Recommended max. PV power	3.75 kW	4.5 kW	5.4 kW	6 kW	6.9 kW	7.5 kW	9 kW
Max. input voltage	550 V	600 V					
Rated voltage	250 V	330 V					
Start-up voltage	60 V	120 V					
MPPT voltage range	50-450 V	90-520 V					
Max. input current	14 A / 14 A						
Max. short circuit current	22 A / 22 A						
MPPT number/Max. input strings number	2/2						

### Output AC

Rated output power	2.5 kW	3 kW	3.6 kW	4 kW	4.6 kW	5 kW	6 kW
Max. apparent output power	2.8 kVA	3.3 kVA	4 kVA	4.4 kVA	5 kVA	5 kVA	6 kVA
Max. output power	2.8 kW	3.3 kW	4 kW	4.4 kW	5 kW	5 kW	6 kW
Rated grid voltage	1/N/PE, 220 V / 230 V						
Rated grid frequency	50 Hz / 60 Hz						
Rated grid output current	11.4 A / 10.9 A	13.6 A / 13.0 A	16.0 A / 15.7 A	18.2 A / 17.4 A	20.9 A / 20.0 A	22.7 A / 21.7 A	27.3 A
Max. output current	13.3 A	15.7 A	16.0 A	21.0 A	23.8 A	25.0 A	27.3 A
Power Factor	>0.99 (0.8 leading - 0.8 lagging)						
THDi	<3%						

### Efficiency

Max. efficiency	97.3%	97.3%	97.6%			97.7%
EU efficiency	96.5%	96.6%	97.1%			97.1%

### Protection

DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	Yes
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Integrated AFCI (DC arc-fault circuit protection)	Yes <sup>(1)</sup>
Integrated DC switch	Optional

### General Data

Dimensions (W*H*D)	310*543*160 mm						
Weight	11 kg	11.2 kg			12 kg		
Topology	Transformerless						
Self consumption (night)	<1 W						
Operating ambient temperature range	-25 ~ +60°C						
Relative humidity	0-100%						
Ingress protection	IP66						
Cooling concept	Natural convection						
Max. operation altitude	4000 m						
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA						
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-3						

### Features

DC connection	MC4 connector
AC connection	Quick connection plug
Display	LCD
Communication	RS485, Optional: Wi-Fi, GPRS

(1) Activation required.



Product Service

# Attestation of Conformity

No. N8A 086470 0020 Rev. 05

**Holder of Certificate:** **Ginlong Technologies Co., Ltd.**

No.57 Jintong Road  
Binhai Industrial Park, Xiangshan  
315712 Ningbo, Zhejiang  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Converter**  
**PV Grid-Tied Inverter**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704091623704-05

**Date,** 2021-08-17

( Zhengdong Ma )

Page 1 of 6

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



# Attestation of Conformity

No. N8A 086470 0020 Rev. 05

**Model(s):** Solis-1P2.5K-4G, Solis-1P3K-4G, Solis-1P3.6K-4G, Solis-1P4K-4G, Solis-1P4.6K-4G, Solis-1P5K-4G-MX, Solis-1P5K-4G, Solis-1P6K-4G, Solis-1P2.5K-4G-C, Solis-1P3K-4G-C, Solis-1P3.6K-4G-C, Solis-1P4K-4G-C, Solis-1P4.6K-4G-C, Solis-1P5K-4G-MX-C, Solis-1P5K-4G-C, Solis-1P6K-4G-C, S5-GR1P2.5K, S5-GR1P3K, S5-GR1P3.6K, S5-GR1P4K, S5-GR1P4.6K, S5-GR1P5K, S5-GR1P6K, S6-GR1P2.5K, S6-GR1P3K, S6-GR1P3.6K, S6-GR1P4K, S6-GR1P4.6K, S6-GR1P5K, S6-GR1P6K, S6-GR1P2.5K-R, S6-GR1P3K-R, S6-GR1P3.6K-R, S6-GR1P4K-R, S6-GR1P4.6K-R, S6-GR1P5K-R, S6-GR1P6K-R.

## Parameters:

Models	Solis-1P2.5K-4G Solis-1P2.5K-4G-C	Solis-1P3K-4G Solis-1P3K-4G-C	Solis-1P3.6K-4G Solis-1P3.6K-4G-C	Solis-1P4K-4G Solis-1P4K-4G-C
PV input ratings:				
Max. input voltage:	550Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	50-450Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.
Isc PV (absolute maximum):	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	2500W	3000W	3600W	4000W
Max. AC output active power:	2800W	3300W	4000W	4400W
Max. AC output apparent power:	2800VA	3300VA	4000VA	4400VA
Max. continuous output current:	13.3Aa.c.	15.7Aa.c.	16Aa.c.	21Aa.c.



Product Service

# Attestation of Conformity

No. N8A 086470 0020 Rev. 05

Page 3 of 6

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



# Attestation of Conformity

No. N8A 086470 0020 Rev. 05

Models	Solis-1P4.6K-4G Solis-1P4.6K-4G-C	Solis-1P5K-4G Solis-1P5K-4G-C	Solis-1P5K-4G- MX Solis-1P5K-4G- MX-C	Solis-1P6K-4G Solis-1P6K-4G-C
PV input ratings:				
Max. input voltage:	600Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.
Isc PV (absolute maximum):	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	4600W	5000W	4999W	6000W
Max. AC output active power:	5000W	5000W	4999W	6000W
Max. AC output apparent power:	5000VA	5000VA	4999VA	6000VA
Max. continuous output current:	23.8Aa.c.	25Aa.c.	21.7Aa.c.	27.3Aa.c.



Product Service

# Attestation of Conformity

No. N8A 086470 0020 Rev. 05

Models	S5-GR1P2.5K S6-GR1P2.5K S6-GR1P2.5K-R	S5-GR1P3K S6-GR1P3K S6-GR1P3K-R	S5-GR1P3.6K S6-GR1P3.6K S6-GR1P3.6K-R	S6-GR1P4K S6-GR1P4K S6-GR1P4K-R
PV input ratings:				
Max. input voltage:	550Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	50-450Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	2500W	3000W	3600W	4000W
Max. AC output active power:	2800W	3300W	4000W	4400W
Max. AC output apparent power:	2800VA	3300VA	4000VA	4400VA
Max. continuous output current:	13.3Aa.c.	15.7Aa.c.	16Aa.c.	21Aa.c.



Product Service

# Attestation of Conformity

No. N8A 086470 0020 Rev. 05

Models	S5-GR1P4.6K S6-GR1P4.6K S6-GR1P4.6K-R	S5-GR1P5K S6-GR1P5K S6-GR1P5K-R	S5-GR1P6K S6-GR1P6K S6-GR1P6K-R
Max. input voltage:	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz
Rated output power:	4600W	5000W	6000W
Max. AC output active power:	5000W	5000W	6000W
Max. AC output apparent power:	5000VA	5000VA	6000VA
Max. continuous output current:	23.8Aa.c.	25Aa.c.	27.3Aa.c.

General specifications:		
Models	S6 series moldes	all other models
Adjustable cos( $\varphi$ )	-0.8...1...+0.8	
Protection class	I	
Degree of protection	IP66	IP65
Overvoltage category	II(PV), III(MAINS)	
Ambient temperature	-25°C ... +60°C	
Inverter topology	Non-isolated	

**Tested according to:**

EN 62109-1:2010  
EN 62109-2:2011



**C E R T I F I C A T E**  
of Conformity



**Registration No.:** AK 50514285 0001

**Report No.:** CN20G2DH 002

**Holder:** Ginlong technologies Co., Ltd.  
No.57 Jintong Road, Binhai,  
(seafront), Industrial Park,  
Xiangshan Ningbo  
315712 Zhejiang  
P.R. China

**Product:** PV-Inverter  
(Grid-Connected PV Inverter)

**Identification:** Type Designation: S6-GR1PxxK (xx=2.5,3,3.6,4,4.6,5,6)  
Solis-1Pxxk-4G (xx=2.5,3,3.6,4,4.6,5,6)  
Firmware Version: V2F  
Serial Number : Engineering Samples  
Remark : Refer to test report CN20G2DH 002 for detail.

**Tested acc. to:** IEC 61727:2004  
IEC 62116:2014

The certificate of conformity refers to the above mentioned product. This is to certify that the specimen is in conformity with the assessment requirement mentioned above. This certificate does not imply assessment of the production of the product and does not permit the use of a TÜV Rheinland mark of conformity.

**Date** 27.08.2021



**Weichun Li**

**TÜV Rheinland LGA Products GmbH - Tillystraße 2 - 90431 Nürnberg**

Ginlong technologies Co., Ltd.  
Zhang Kun

Date : 27.08.2021  
Our ref. : LIUPHI 01  
Your ref.: Z.K

No.57 Jintong Road, Binhai,  
(seafront), Industrial Park,  
Xiangshan Ningbo  
315712 Zhejiang  
P.R. China

**Ref : AK Certificate of Conformity**

Type of Equipment : Grid-Connected PV Inverter  
Model Designation : See Certificate  
Certificate No. : AK 50514285 0001  
Report No. : CN20G2DH 002

Dear Zhang Kun,


We herewith confirm that a sample of the above mentioned technical equipment has been tested and was found to be in accordance with the relevant requirements.

Enclosed please find your Certificate of Conformity.

We appreciate your kind support and would like to offer our assistance and continuous services in the future.

With kind regards,

Certification Body

  
Weichun Li

Enclosure

证书的详细资料请登陆[www.certipedia.com](http://www.certipedia.com)查阅,或拨打我司客服热线800 999 3668 / 400 883 1300咨询